



Vision ESPlus Bluetec V8

Big size multi-products vending

ESPLUS R290 V8 ESPLUS REFRIGER V8 ESPLUS AMBIENT V8

TECHNOLOGICAL INNOVATION • RELIABILITY • 100% JOFEMAR TECHNOLOGY

The Vision ESPlus is the perfect solution for dispensing of products because it's optimised capacity. It features up to 8 trays of up to 10 channels each, big elevator and optionally, a cooling unit. Versatility in its connection by the control unit allows significantly increasing the number of channels and the overall storage capacity to vend almost any type of products at point of sale.



REGULATION (EU) 2019/2018



VANDAL-PROOF LOCK



OPTIMISED CAPACITY AND VOLUME





FASYFIFX DELIVERY SYSTEM



PRODUCT DELIVERY DETECTION **PHOTOCELLS**





- Temperature: with or without cooling unit.
- Capacity up to 8 trays of up to 10 height adjustable
- FIFO (First In First Out) System. Product dispensing according to loading order.
- · Correct sale detection with photocells.
- · LED lighting system with on/off programming.
- 1.169 x 714 mm glass front door.
- Continuous performance self-testing.
- Health timer to prevent selling out-of-date products. Programmable expiration date by selection or channel.
- Flexible setup programming. Its channel adjustment system allows incorporating new products at any time without using tools.
- Inteligent self-adjusting motor torque for each type of product characteristics, optional manual motor torque adjustment.
- Power mains: 230 V, 50 Hz.
- · Assigned power, R290 model: 300 watts.
- Assigned power, Refriger model: 340 watts.
- · Assigned power, Ambient model: 30 watts.
- · Large capacity elevator.
- Multi-sales system, able to deliver several products in a single elevator maneuver.

STRUCTURE

- Modular cabinet structure treated against rust and corrosion
- · Vandal-proof security lock with three anchor points.
- Injected foam insulation system to guarantee efficient cooling and lower energy consumption.

CREDIT MANAGEMENT

- Through the control unit, Vision or Coffeemar machines.
- •Through the payment pod.

PROGRAMMING

- Through the control unit, Vision or Coffeemar machines.
- Through the payment pod.

OPTIONS

- · Cooling unit can be fitted.
- A see thru elevator.





	ESPLUS R290 V8
Temperature	With/Without cooling unit
Maximum capacity	Up to 8 trays of max. 10 channels
Elevator	Yes
Size (mm)	1.835 x 800 x 1.025
Weight	352 kg
Energy supply	230 V, 50 Hz*
Cooling unit	Optional

*Check for other voltages.



Ctra. Marcilla km 2 31350 PERALTA. Navarra SPAIN Tel. +34 948 75 12 12 Fax +34 948 75 04 20

